

Thank you for choosing the PS106 Audiophile Power Management and Purification System.

This unit has been designed and constructed with care and attention to every detail and will provide very many years of service. We are always on hand to advise on any aspect of use.

The unit is designed to be permanently powered. No indicator light is employed as the electrical noise generated by led or neon indicators is contrary to the aims of this unit.

The additional earthing terminal on the unit is directly connected to the filtered star earthing point as used by each socket outlet and may be used to provide additional access to the star earth point for non- mains connected accessories, e.g. tone arms.

The input is protected against over current use by means of a resettable trip located just below the additional earthing terminal. If the protector trips check all connected equipment before pressing to reset.

With the PS106 installed definition takes an enormous stride forward, individual instruments gain air between them, their sound and timbre becomes believable, the soundstage moves out from the speakers and into the room with gains in three dimensionality with clarity and definition, the instruments interrelate with, rather than muddle each other. Your listening becomes a more engaging and pleasurable experience. Visual equipment performs to a higher level of noiseless richness and definition.

- **Heavily constructed electrically and magnetically shielded casing**
- **Six independently filtered 10 amp outlets avoid cross contamination**
- **Multiple cumulative stages of purification removes common and differential mode interference**
- **Direct maximum power, equal resistance routing to all outputs**
- **Massive 9,000 amps of three dimensional non-sacrificial surge protection guards your valuable equipment against lightning damage etc.**
- **Star earthing plan avoids hum loops, reduces the noise floor, for greater silence and definition**
- **Cleansed earth removes noise from the earth line further enhancing clarity and dynamics**
- **Internal wiring silver plated OFC copper PTFE insulation**
- **Dimensions in mm W 540 D 87 H 90 4 Kgs**
- **Rated Voltage 110-240 50-60Hz**
- **IEC type C20 Input**
- **3 Years Guarantee**

Note: Schuko versions have live polarity indicated on socket outlets and plugs with a RED DOT.

on We know that you will receive much enjoyment from the use of this equipment and would very much like to hear of your experiences.

You have got the noise out – Don't let it back in between this box and your equipment!!! Puritan Dissipative Technology Mains Cables "eat" interference and absorb vibration distortion.